

## Patent Abstracts of Japan

PUBLICATION NUMBER : 11099512  
PUBLICATION DATE : 13-04-99

APPLICATION DATE : 30-09-97  
APPLICATION NUMBER : 09264713

APPLICANT : KUBOTA CORP;

INVENTOR : UEMATSU ATSUSHI;

INT.CL. : B28B 5/02 B28B 3/02 B28B 11/14 C04B 28/18 //(C04B 28/18 , C04B 14:18 ,  
C04B 22:06 , C04B 16:02 ) C04B111:20

TITLE : MANUFACTURE OF FIBER REINFORCED CEMENT PLATE

ABSTRACT : PROBLEM TO BE SOLVED: To realize the stronger plane tensile strength of a surface layer and, at the same time, heighten the working strength after its primary curing by easily giving a deep-engraved uneven pattern to the surface of a cement plate by a method wherein a micro-bubble-containing surface layer is provided.

SOLUTION: In a single layer flow-on molding method, in which a plate is produced by laminarily feeding a cement slurry mixed with a suction dehydrating device and, after being suction-dehydrated, embossably pressed, 2-10 wt.% of silica fume or crystalline silica having the specified surface area of cement by blaine of 8,000 cm<sup>2</sup>/g or finer is added to the cement slurry prepared by mixing micro-bubbles. Instead, a process, in which 75-200 g of a silica fume aqueous solution per the square meters of the surface of the cement slurry layer mixed with micro-bubbles before pressing is sprayed on the surface of the cement slurry and then embossably pressed, is prepared.

COPYRIGHT: (C)1999,JPO